






OK-pack® ECOBlack

Closed cell non crosslinked PE foam extruded profiles for industrial packaging applications.

- Contains minimum 60% recycled material.
- 100% reusable and recyclable.



Reference	A (mm)	B (mm)	C (mm)	L (cm)	d (Kg/m ³)	m/box	Type
U20 EB	20±1,5	30±2	8±1	200±4	28±5	520	2
U25 EB	24±3	37±2	10±1	200±4	28±5	380	2
U30 EB	30±2	44±3	11±1	200±4	28±5	250	2
U30/90 EB	29±2	95±6	14±1	200±4	28±5	100	4
U35 EB	35±3	40±3	10±1	200±4	28±5	240	2
U45EB	45±2.5	45±3	12±1	200±4	28±5	180	2
U60 EB	60±3	60±3	13±1	200±4	28±5	120	2
U70 EB	70±3	63±3	15±1	200±4	28±5	90	2
U72/120 EB	79±5	120±5	17±2	200±4	28±5	60	5
U80 EB	80±2	72±3	18±2	200±4	28±5	80	2
U90 EB	90±3	80±5	18±2	200±4	28±5	72	6
U100 EB	100±3	70±5	18±2	200±4	28±5	56	6
U120 EB	120±4	80±5	20±2	200±4	28±5	44	6
L50 EB	50±4	7±1		200±4	28±5	460	
L50plus EB	50±4	10±1		200±4	28±5	350	
L75 EB	75±7	11±1		200±4	28±5	210	



Microlen ECOBlack

- Crosslinked closed cell polyethyelene foam blocks.
- Contains minimum 30% recycled material.
- 100% reusable and recyclable.



Contains min. 30% recycled material

Microlen ECOGreen

- Crosslinked closed cell, 100% renewable, biopolymer foam blocks.
- 100% recyclable and reusable.



Biopolymer 100% renewable



	Density (kg/m3)	length (mm)	width (mm)	Thickness (mm)	Color
PEQ 28XL EB	28	2400	1200	105	Antracite
PEQ 35XL EB	35	2400	1200	105	Antracite
PEQ 35XL EG	35	2400	1200	105	Various
PE45X DB EG	45	2000	1000	105	Deep Black



JANUARY 2023



OVERSEAS KONSTELLATION
COMPANY S.A.

P.I. La Serra II. 25320 Anglesola—Lleida
Tlf: +34-973308518.

www.okcompany.com / infotec@okcompanysa.com